

## RD SERIES

### FEATURES

- **Radome diameters**
  - 2' (60 cm)
  - 3' (90 cm)
  - 4' (120 cm)
  - 6' (180 cm)
- **Radome weights**
  - 2' 4 lbs. (1.8 kg)
  - 3' 8 lbs. (3.6 kg)
  - 4' 20 lbs. (9.0 kg)
  - 6' 30 lbs. (13.5 kg)
- **Factory installed** prior to shipping  
(6 ft radome shipped loose)
- **Reduces wind loading** on the tower or associated antenna structure
- **Molded radomes** are made of ABS plastic
- U.V. inhibited and protect the antenna from severe environmental conditions
- Radomes are paintable
- Attachment kits are available for existing antennas in the field



### GHz ELECTRICAL SPECIFICATIONS (typical performance)\*

Model Number	Diameter ft. (cm)	Attenuation		Add to antenna VSWR Max.	
		2 GHz	5 GHz	2 GHz	5 GHz
RD2	2 (60)	0.2	0.4	0.02	0.04
RD3	3 (90)	0.2	0.4	0.02	0.04
RD4	4 (120)	0.2	0.4	0.02	0.04
RD6	6 (180)	0.2	0.4	0.02	0.04

\* All specifications subject to change without notice.